www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO THT FEMALE HEADER; 0.9 X 0.9 MM SOLDER PIN; STRAIGHT; 100% PROTECTED AGAINST MISMATING; LOCKING LEVER; PIN SPACING 3.81 MM; 3-POLE; ORANGE

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 160; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tesiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 10; A
Tensiune nominala CSA (Use Group D): 300; V
Curent nominal CSA (Use Group D): 10; A
Numar poli: 3;
Numar total de conexiuni: 3;
Total number of potentials: 3;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3.81 mm / 0.15 inch;
Latime: 23.23 mm / 0.915 inch;

Inaltime: 18.5 mm / 0.728 inch;
Inaltime de la fata: 14.7 mm / 0.579 inch;
Adancime: 10.5 mm / 0.413 inch;
Lungimea pinului de contact: 3,8; mm
Solder pin dimensions: 0.9 x 0.9 mm;
Diametrul de gaurire cu toleranta: 1.4 (+0.1) mm;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for PCBs;
Mismating protection: Yes;
Mating direction to the PCB: 90; °
Locking of plug-in connection: locking lever;
PCB contact: THT;
Solder pin arrangement: over the entire female connector, in line;
Number of solder pins per potential: 1;
Culoare: orange;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Copper alloy;
Contact plating: tin-plated;
Fire load: 0,045; MJ
Greutate: 2,2; g
Temperatura lucru: -60 … +100 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454029456;
Customs tariff number: 85366990990;
Pret: 11,69 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/tht-female-header-0-9-x-0-9-mm-solder-pin-straight-100-protected-against-mismating-locking-lever-pin-spacing-3-81-mm-3-pole-orange-133924