



**WAGO THR MALE HEADER; 0.8 X 0.8 MM SOLDER PIN; STRAIGHT; 100%  
PROTECTED AGAINST MISMATING; IN TAPE-AND-REEL PACKAGING; PIN  
SPACING 2.5 MM; 7-POLE; BLACK**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 80; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 6; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 150; V

Curent nominal UL (Use Group B): 4; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 150; V

Curent nominal CSA (Use Group B): 4; A

Numar poli: 7;

Total number of potentials: 7;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 2.5 mm / 0.098 inch;

Latime: 20 mm / 0.787 inch;

Inaltime: 11.3 mm / 0.445 inch;

Inaltime de la fata: 8.9 mm / 0.35 inch;

Adancime: 7.8 mm / 0.307 inch;

Lungimea pinului de contact: 2,4; mm

Solder pin dimensions: 0.8 x 0.8 mm;

Diametru placat prin gaura (THR): 1.2 (+0.1) mm;  
Reel diameter of tape-and-reel packaging: 330; mm  
Tape Latime: 44; mm  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for PCBs;  
Mismating protection: Yes;  
Mating direction to the PCB: 90; °  
PCB contact: THR;  
Solder pin arrangement: over the entire male connector, in line;  
Number of solder pins per potential: 1;  
Culoare: black;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,025; MJ  
Greutate: 1,1; g  
Temperatura lucru: -60 ... +100 °C;  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4045454814526;  
Customs tariff number: 85366990990;  
Pret: 13,11 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismating-in-tape-and-reel-packaging-pin-spacing-2-5-mm-7-pole-black-134194>