



**WAGO THR MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN; ANGLED; 100%
PROTECTED AGAINST MISMATING; IN TAPE-AND-REEL PACKAGING; PIN
SPACING 3.5 MM; 2 X 18-POLE; BLACK**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 80; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 250; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 150; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group C): 50; V

Curent nominal UL (Use Group C): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 150; V

Curent nominal CSA (Use Group B): 12; A

Numar poli: 36;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 2;

Distanta intre pini: 3.5 mm / 0.138 inch;

Latime: 73.1 mm / 2.878 inch;

Inaltime: 15.7 mm / 0.618 inch;

Inaltime de la fata: 13.3 mm / 0.524 inch;

Adancime: 13.5 mm / 0.531 inch;

Lungimea pinului de contact: 2,4; mm
Solder pin dimensions: 0.8 x 0.8 mm;
Diametru placat prin gaura (THR): 1.3 (+0.1) mm;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 88; mm
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCBs;
Mismating protection: Yes;
Mating direction to the PCB: 0; °
Locking of plug-in connection: Threaded flange;
PCB contact: THR;
Solder pin arrangement: over the entire male connector, in line;
Number of solder pins per potential: 1;
Culoare: black;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 11; g
Temperatura lucru: -60 ... +100 °C;
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4055143778916;
Customs tariff number: 85366990990;
Pret: 60,35 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-2-row-0-8-x-0-8-mm-solder-pin-angled-100-protected-against-mismating-in-tape-and-reel-packaging-pin-spacing-3-5-mm-2-x-18-pole-black-134803>