



WAGO THR MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN; STRAIGHT; 100% PROTECTED AGAINST MISMATCHING; PIN SPACING 3.5 MM; 2 X 14-POLE; BLACK

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 80; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 250; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 150; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group C): 50; V

Curent nominal UL (Use Group C): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 150; V

Curent nominal CSA (Use Group B): 12; A

Numar poli: 28;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 2;

Distanta intre pini: 3,5 mm / 0.138 inch;

Latime: 50,5 mm / 1.988 inch;

Inaltime: 15,9 mm / 0.626 inch;

Inaltime de la fata: 13,5 mm / 0.531 inch;

Adancime: 13,3 mm / 0.524 inch;

Lungimea pinului de contact: 2,4; mm

Solder pin dimensions: 0,8 x 0,8 mm;
Diametru placat prin gaura (THR): 1,3 (+0,1) mm;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCB;
Mismating protection: Yes;
Mating direction to the PCB: 90; °
PCB contact: THR;
Solder pin arrangement: over the entire male connector (in-line);
Number of solder pins per potential: 1;
Culoare: black;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,146; MJ
Greutate: 7; g
Temperatura lucru: -60 ... +100 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4050821155775;
Customs tariff number: 85366990990;
Pret: 39,76 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-2-row-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismating-pin-spacing-3-5-mm-2-x-14-pole-black-134981>