www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 1-CONDUCTOR FEMALE CONNECTOR, 2-ROW; 100% PROTECTED AGAINST MISMATING; STRAIN RELIEF PLATE; DIRECT MARKING; 1.5 MM²; PIN SPACING 3.5 MM; 18-POLE; 1,50 MM²; BLACK

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 80; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tesiune nominala (II/2): 250; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group C): 50; V
Curent nominal UL (Use Group C): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 10; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Solid conductor: 0.08 … 1.5 mm² / 28 … 16 AWG;
Fine-stranded conductor: 0.08 … 1.5 mm² / 28 … 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0.25 … 1 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0.25 … 1 mm²;
Strip length: 6 … 7 mm / 0.24 … 0.28 inch;
Numar poli: 18;
Numar total de conexiuni: 18;

Total number of potentials: 18;
Numar tipuri de conexiuni: 1;
Numar nivele: 2;
Conductor entry direction to mating direction: 0; °
Distanta intre pini: 3.5 mm / 0.138 inch;
Latime: 33 mm / 1.299 inch;
Inaltime: 43.7 mm / 1.72 inch;
Adancime: 16 mm / 0.63 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductors;
Mismating protection: Yes;
Strain relief: strain relief plate;
Culoare: black;
Material group: II;
Material izolator: Glass fiber-reinforced polyamide (PA 66 GF);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy;
Contact plating: tin-plated;
Fire load: 0,161; MJ
Greutate: 10,1; g
Temperatura lucru: -60 … +100 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4050821176947;
Customs tariff number: 85366990990;
Pret: 75,87 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/1-conductor-female-connector-2-row-100-protected-against-mismating-strain-relief-plate-direct-marking-1-5-mm2-pin-spacing-3-5-mm-18-pole-1-50-mm2-black-135192