
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO LIGHTING CONNECTOR; PUSH-BUTTON, EXTERNAL; FOR LINECT®; WITH ANGLED SNAP-IN GROUND CONTACT; 1/L´-2/L-PE-N; 4-POLE; COD. A; LIGHTING SIDE: FOR SOLID CONDUCTORS; INST. SIDE: FOR ALL CONDUCTOR TYPES; MAX. 2.5 MM²; SURROUNDING AIR TEMPERATURE: MAX 85°C (T85);

Ratings per: IEC/EN 60998-1;
Ratings (note): Connection points;
Tesiune nominala (II/2): 500; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 24; A
Ratings per: IEC/EN 60998-2-2;
Ratings (note) 2: Connection points;
Tensiune nominala (II/2) 2: 500; V
Tensiune nominala de supratensiune (II/2) 2: 4; kV
Curent nominal 2: 24; A
Ratings per (3): IEC/EN 61984;
Ratings (note) 3: Linect® plug-in connection;
Tensiune nominala (II/2) 3: 500; V
Tensiune nominala de supratensiune (II/2) (3): 4; kV
Curent nominal 3: 16; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Connection type (1): External 1;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Number of connection points (connection type): 2;
Tip actionare: Push-button;
Tip actionare 2: Push-in;
Solid conductor: 0,5 … 2,5 mm² / 18 … 12 AWG;
Solid conductor; push-in termination: 0,5 … 2,5 mm² / 18 … 12 AWG;

Stranded conductor: 0,5 … 2,5 mm² / 18 … 14 AWG;
Fine-stranded conductor: 0,5 … 2,5 mm² / 18 … 14 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 … 1,5 mm² / 18 … 16 AWG;
Fine-stranded conductor; with uninsulated ferrule: 0,5 … 1,5 mm² / 18 … 16 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,5 mm² / 18 AWG;
Strip length: 8 … 9 mm / 0.31 … 0.35 inch;
Numar poli: 4;
Connection type 2: Internal 2;
Tehnologie conexiune 2: PUSH WIRE®;
Number of connection points: 1;
Solid conductor 2: 0,5 … 2,5 mm² / 18 … 14 AWG;
Fine-stranded conductor; with insulated ferrule 2: 0,5 … 1 mm² / 18 … 14 AWG;
Fine-stranded conductor; with uninsulated ferrule 2: 0,5 … 1,5 mm² / 18 … 16 AWG;
Strip length 2: 8 … 9 mm / 0.31 … 0.35 inch;
Connection type (3): Internal 3;
Tehnologie conexiune 3: PUSH WIRE®;
Number of connection points: 1;
Tip actionare 3: Push-in;
Solid conductor 3: 0,5 … 1,5 mm² / 18 … 16 AWG;
Fine-stranded conductor; with insulated ferrule 3: 0,5 … 0,75 mm² / 18 AWG0.5 … 0.75mm² / 18 AWG;
Fine-stranded conductor; with uninsulated ferrule 3: 0,5 … 1 mm² / 18 … 14 AWG;
Strip length 3: 8 … 9 mm / 0.31 … 0.35 inch;
Connection type (4): Internal 4;
Tehnologie conexiune 4: PUSH WIRE®;
Number of connection points: 1;
Tip actionare 4: Push-in;
Solid conductor 4: 0,5 … 0,75 mm² / 18 AWG;
Strip length (4): 8 … 9 mm / 0.31 … 0.35 inch;
Total number of potentials: 4;
Numar tipuri de conexiuni: 4;
Ground function: with angled snap-in ground contact;
Distanta intre pini: 10 mm / 0.394 inch;
Latime: 40 mm / 1.575 inch;
Inaltime: 22,4 mm / 0.882 inch;
Inaltime de la fata: 17 mm / 0.669 inch;
Adancime: 27,3 mm / 1.075 inch;
Technologie: Linect;
Marking: 1/L' 2/L ? N;
Culoare: white;
Material group: III a;
Material izolator: Polycarbonate (PC);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,265; MJ
Greutate: 14; g
Temperature stability: 120; °C
T marking: T85;
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: bag;
Tara de origine: PL;
GTIN: 4050821098898;
Customs tariff number: 85369010000;

Pret: 6,74 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lighting-connector-push-button-external-for-linect-with-angled-snap-in-ground-contact-1-l-2-l-pe-n-4-pole-cod-a-lighting-side-for-solid-conductors-inst-side-for-all-conductor-types-max-2-5-mm2-surrounding-air-temperature-max-850c-t85-2-50-mm2-white-135281