



**WAGO PCB TERMINAL BLOCK; LEVER; 6 MM<sup>2</sup>; PIN SPACING 10 MM; 9-POLE;  
CAGE CLAMP®; 6,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Tensiune nominala (III/2): 1000; V  
Tensiune nominala de supratensiune (III/2): 8; kV  
Tensiune nominala (II/2): 1000; V  
Tensiune nominala de supratensiune (II/2): 8; kV  
Curent nominal: 41; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group B): 300; V  
Curent nominal UL (Use Group B): 30; A  
Tensiune nominala UL (Use Group C): 150; V  
Curent nominal UL (Use Group C): 30; A  
Tensiune nominala UL (Use Group D): 600; V  
Curent nominal UL (Use Group D): 5; A  
Certificari: UL 1059;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Lever;  
Solid conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Fine-stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,5 ... 6 mm<sup>2</sup>;  
Fine-stranded conductor; with uninsulated ferrule: 0,5 ... 6 mm<sup>2</sup>;  
Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;  
Conductor connection direction to PCB: 30; °  
Numar poli: 9;  
Numar total de conexiuni: 9;

Total number of potentials: 9;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 10 mm / 0.394 inch;  
Latime: 85 mm / 3.346 inch;  
Inaltime: 30 mm / 1.181 inch;  
Inaltime de la fata: 25,5 mm / 1.004 inch;  
Adancime: 26 mm / 1.024 inch;  
Lungimea pinului de contact: 4,5; mm  
Solder pin dimensions: 1 x 1,4 mm;  
Diametrul de gaurire cu toleranta: 1,8 (+0,1) mm;  
PCB contact: THT;  
Solder pin arrangement: over the entire terminal strip (in-line);  
Number of solder pins per potential: 2;  
Culoare: gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ESu);  
Contact plating: tin-plated;  
Fire load: 1,079; MJ  
Greutate: 54,4; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4050821093299;  
Customs tariff number: 85369010000;  
Pret: 61,63 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-lever-6-mm2-pin-spacing-10-mm-9-pole-cage-clamp-6-00-mm2-gray-135670>