



Image coming soon

**WAGO 2-CONDUCTOR TERMINAL STRIP; SUITABLE FOR EX E II APPLICATIONS;  
11-POLE; WITHOUT PUSH-BUTTONS; WITH SNAP-IN MOUNTING FEET; FOR PLATE  
THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50  
MM<sup>2</sup>; LIGHT GRAY**

Tensiune nominala EN (Ex e II): 690; V  
Curent nominal (Ex e II): 23; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 11;  
Numar total de conexiuni: 2;  
Total number of potentials: 11;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 73 mm / 2.874 inch;  
Inaltime de la fata: 22.1 mm / 0.87 inch;  
Adancime: 32 mm / 1.26 inch;  
Module Latime: 6 mm / 0.236 inch;  
Design: horizontal;  
Marking level: Center marking;  
Culoare: light gray;  
Fire load: 0,87; MJ  
Greutate: 45,9; g  
Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918423342;  
Customs tariff number: 85369010000;  
Pret: 54,28 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-terminal-strip-suitable-for-ex-e-ii-applications-11-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-light-gray-135774>