



Image coming soon

**WAGO 2-CONDUCTOR TERMINAL STRIP; SUITABLE FOR EX E II APPLICATIONS;  
3-POLE; WITHOUT PUSH-BUTTONS; WITH SNAP-IN MOUNTING FEET; FOR PLATE  
THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; 4 MM<sup>2</sup>; CAGE CLAMP®; 4,00 MM<sup>2</sup>;  
LIGHT GRAY**

Tensiune nominala EN (Ex e II): 550; V  
Curent nominal (Ex e II): 23; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Numar poli: 3;  
Numar total de conexiuni: 6;  
Total number of potentials: 3;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 25.4 mm / 1 inch;  
Inaltime de la fata: 23 mm / 0.906 inch;  
Adancime: 33.5 mm / 1.319 inch;  
Module Latime: 7 mm / 0.276 inch;  
Design: horizontal;  
Tip montaj: Snap-in mounting foot;  
Marking level: Side marking;  
Culoare: light gray;  
Fire load: 0,283; MJ  
Greutate: 13,8; g  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4044918642026;  
Customs tariff number: 85369010000;  
Pret: 13,11 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-terminal-strip-suitable-for-ex-e-ii-applications-3-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-4-mm2-cage-clamp-4-00-mm2-light-gray-135992>