



**WAGO 2-CONDUCTOR TERMINAL STRIP; 5-POLE; WITHOUT PUSH-BUTTONS;
WITH SNAP-IN MOUNTING FEET; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING
HOLE 3.5 MM Ø; 4 MM²; CAGE CLAMP®; 4,00 MM²; GRAY**

Tesiune nominala (III/3): 630; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Numar poli: 5;

Numar total de conexiuni: 10;

Total number of potentials: 5;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 39.4 mm / 1.551 inch;

Inaltime de la fata: 23 mm / 0.906 inch;

Adancime: 33.5 mm / 1.319 inch;

Module Latime: 7 mm / 0.276 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,422; MJ

Greutate: 21,8; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918642347;
Customs tariff number: 85369010000;
Pret: 20,16 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-terminal-strip-5-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-4-mm2-cage-clamp-4-00-mm2-gray-136004>