www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 2-POLE; N-L1; WITHOUT GROUND CONTACT; FOR SELF-TAPPING SCREW 2.9 MM Ø FROM BELLOW; WITH 2X PIN; 4 MM²; 4,00 MM²; WHITE

Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 32; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool; Push-button;
Connectable conductor materials: Copper;
Solid conductor: 0,5 … 4 mm² / 20 … 12 AWG;
Solid conductor; push-in termination: 0,75 … 4 mm² / 18 … 12 AWG;
Stranded conductor: 0,5 … 4 mm² / 20 … 12 AWG;
Fine-stranded conductor: 0,5 … 4 mm² / 20 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 … 2,5 mm² / 20 … 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm² / 18 AWG;
Strip length: 10 … 11 mm / 0.39 … 0.43 inch;
Numar poli: 2;
Numar total de conexiuni: 8;
Total number of potentials: 2;
Wiring type: Side-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Distanta intre pini: 12 mm / 0.472 inch;
Latime: 24 mm / 0.945 inch;
Inaltime de la fata: 22,3 mm / 0.878 inch;
Adancime: 35 mm / 1.378 inch;
Tip montaj: Screw mounting;

Marking: N-L1;
Culoare: white;
Fire load: 0,267; MJ
Greutate: 14,1; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918510318;
Customs tariff number: 85369010000;
Pret: 9,27 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-2-pole-n-l1-without-ground-contact-for-self-tapping-screw-2-9-mm-oe-from-bellow-with-2x-pin-4-mm2-4-00-mm2-white-136189