



**WAGO THT MALE HEADER; 1.0 X 1.2 MM SOLDER PIN; ANGLED; 100%
PROTECTED AGAINST MISMATING; PIN SPACING 7.62 MM; 9-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Tensiune nominala (III/2): 630; V

Tensiune nominala de supratensiune (III/2): 6; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 6; kV

Curent nominal: 41; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 42; A

Tensiune nominala UL (Use Group D): 600; V

Curent nominal UL (Use Group D): 5; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 41; A

Tensiune nominala CSA (Use Group D): 600; V

Curent nominal CSA (Use Group D): 5; A

Numar poli: 9;

Total number of potentials: 9;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 7.62 mm / 0.3 inch;

Latime: 71.46 mm / 2.813 inch;

Inaltime: 18.8 mm / 0.74 inch;

Inaltime de la fata: 14.8 mm / 0.583 inch;

Adancime: 29 mm / 1.142 inch;
Lungimea pinului de contact: 4; mm
Solder pin dimensions: 1 x 1.2 mm;
Diametrul de gaurire cu toleranta: 1.7 (+0.1) mm;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCBs;
Mismating protection: Yes;
Mating direction to the PCB: 0; °
PCB contact: THT;
Solder pin arrangement: over the entire male connector, in line;
Number of solder pins per potential: 3;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 23; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4055143589444;
Customs tariff number: 85366990990;
Pret: 38,65 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-1-0-x-1-2-mm-solder-pin-angled-100-protected-against-mismating-pin-spacing-7-62-mm-9-pole-light-gray-136227>