



**WAGO PCB TERMINAL BLOCK; PUSH-BUTTON; 2.5 MM²; PIN SPACING 7.5/7.62 MM;
7-POLE; SUITABLE FOR EX-I APPLICATIONS; CAGE CLAMP®; COMMONING
OPTION; 2,50 MM²; BLUE**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Tensiune nominala (III/2): 630; V

Tensiune nominala de supratensiune (III/2): 6; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 15; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Finger-operated lever;

Solid conductor: 0,08 ... 2,5 mm² / 25 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1,5 mm²;

Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;

Conductor connection direction to PCB: 90; °
Numar poli: 7;
Numar total de conexiuni: 7;
Total number of potentials: 7;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Note (conductor cross-section): 12 AWG: THHN, THWN;
Distanta intre pini: 7,5/7,62 mm / 0.295/0.3 inch;
Latime: 55,4 mm / 2.181 inch;
Inaltime: 22,2 mm / 0.874 inch;
Inaltime de la fata: 18,2 mm / 0.717 inch;
Adancime: 23 mm / 0.906 inch;
Lungimea pinului de contact: 4; mm
Solder pin dimensions: 0,7 x 0,7 mm;
Diametrul de gaurire cu toleranta: 1,1 (+0,1) mm;
PCB contact: THT;
Solder pin arrangement: over the entire terminal strip (in-line);
Number of solder pins per potential: 2;
Culoare: blue;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,181; MJ
Greutate: 10,4; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4050821848486;
Customs tariff number: 85369010000;
Pret: 14,46 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pcb-terminal-block-push-button-2-5-mm2-pin-spacing-7-5-7-62-mm-7-pole-suitable-for-ex-i-applications-cage-clamp-commoning-option-2-50-mm2-blue-136808>