



**WAGO 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75 MM²; PIN SPACING 5/5.08 MM;
24-POLE; PUSH WIRE®; 0,75 MM²; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Operating tool;

Solid conductor: 0.25 ... 0.75 mm² / 22 ... 18 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Conductor connection direction to PCB: 45; °

Numar poli: 24;

Numar total de conexiuni: 48;

Total number of potentials: 24;

Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 5/5.08 mm / 0.197/0.2 inch;
Latime: 121.5 mm / 4.783 inch;
Inaltime: 20.5 mm / 0.807 inch;
Inaltime de la fata: 16.5 mm / 0.65 inch;
Adancime: 13.5 mm / 0.531 inch;
Lungimea pinului de contact: 4; mm
Solder pin dimensions: 0.5 x 0.75 mm;
Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm;
PCB contact: THT;
Solder pin arrangement: over the entire terminal strip, in line;
Number of solder pins per potential: 2;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,462; MJ
Greutate: 27,5; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918941280;
Customs tariff number: 85369010000;
Pret: 35,47 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-5-5-08-mm-24-pole-push-wire-0-75-mm2-gray-136921>