



**WAGO STACKABLE 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75 MM<sup>2</sup>; PIN SPACING 7.5/7.62 MM; 1-POLE; PUSH WIRE®; 0,75 MM<sup>2</sup>; ORANGE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 400; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Tensiune nominala (III/2): 630; V  
Tensiune nominala de supratensiune (III/2): 6; kV  
Tensiune nominala (II/2): 1000; V  
Tensiune nominala de supratensiune (II/2): 6; kV  
Curent nominal: 10; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group B): 300; V  
Curent nominal UL (Use Group B): 10; A  
Tensiune nominala UL (Use Group D): 300; V  
Curent nominal UL (Use Group D): 10; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group B): 300; V  
Curent nominal CSA (Use Group B): 10; A  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Operating tool;  
Solid conductor: 0.25 ... 0.75 mm<sup>2</sup> / 24 ... 18 AWG;  
Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 0.34 mm<sup>2</sup>;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Conductor connection direction to PCB: 0; °  
Numar poli: 1;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;

Numar nivele: 1;  
Distanta intre pini: 7.5/7.62 mm / 0.295/0.3 inch;  
Latime: 9 mm / 0.354 inch;  
Inaltime: 12.8 mm / 0.504 inch;  
Inaltime de la fata: 9.2 mm / 0.362 inch;  
Adancime: 12.5 mm / 0.492 inch;  
Lungimea pinului de contact: 3,6; mm  
Solder pin dimensions: 0.8 x 0.4 mm;  
Diametrul de gaurire cu toleranta: 1 (+0.1) mm;  
PCB contact: THT;  
Solder pin arrangement: within the terminal block, in line;  
Number of solder pins per potential: 2;  
Culoare: orange;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,01; MJ  
Greutate: 0,6; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4044918832090;  
Customs tariff number: 85369010000;  
Pret: 1,47 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/stackable-2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-7-5-7-62-mm-1-pole-push-wire-0-75-mm2-orange-137357>