



**WAGO DOUBLE PIN HEADER; DIN-35 RAIL MOUNTING; PIN SPACING 5.08 MM; 23-  
POLE; ORANGE**

Ratings per: IEC/EN 60664-1;

Ratings (note): Notice: Male connectors shall not be live when disconnected!;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 12; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 15; A

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 15; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Numar poli: 23;

Total number of potentials: 23;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5.08 mm / 0.2 inch;

Latime: 120.04 mm / 4.726 inch;  
Inaltime from upper-edge of DIN-rail: 15 mm / 0.591 inch;  
Adancime: 42.5 mm / 1.673 inch;  
Tip montaj: DIN-35 rail;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for pluggable connectors;  
Mismating protection: No;  
Culoare: orange;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,393; MJ  
Greutate: 19,8; g  
Temperatura lucru: -60 ... +100 °C;  
Product Group: 3 (Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454340223;  
Customs tariff number: 85366990990;  
Pret: 65,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-pin-header-din-35-rail-mounting-pin-spacing-5-08-mm-23-pole-orange-137763>