



**WAGO FEMALE CONNECTOR FOR RAIL-MOUNT TERMINAL BLOCKS; 0.6 X 1 MM
PINS; ANGLED; PIN SPACING 5 MM; 14-POLE; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 12; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 15; A

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 15; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Numar poli: 14;

Total number of potentials: 14;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 71.5 mm / 2.815 inch;

Inaltime: 26.1 mm / 1.028 inch;
Inaltime de la fata: 11.6 mm / 0.457 inch;
Adancime: 18.25 mm / 0.719 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for front-entry wiring terminal block;
Mismating protection: No;
Mating direction to the rail-mount terminal block: 0; °
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Copper alloy;
Contact plating: tin-plated;
Fire load: 0,26; MJ
Greutate: 14,7; g
Temperatura lucru: -60 ... +85 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143031486;
Customs tariff number: 85366990990;
Pret: 56,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/female-connector-for-rail-mount-terminal-blocks-0-6-x-1-mm-pins-angled-pin-spacing-5-mm-14-pole-gray-138057>