www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 3-POLE; COD. S; 1 M; 1,50 MM²; BROWN

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 23; A
Strip length: 11 mm / 0.43 inch;
Numar poli: 3;
Total number of potentials: 3;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 7,4 … 9,4 mm;
Sectiunea transversala a firului: 1,5; mm²
Strip length (outer insulation): 100; mm
Connection type: Plug - Free end;
Distanta intre pini: 10 mm / 0.394 inch;
Total length: 1; m
Coding: S;
Mating force of a plug-in connection: approx. 20 … 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 20 … 70 N (depending on pole number);
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);
Connection type: Plug - free end;
Type of pre-assembled cable: Connecting cable;

Cable type: H05Z1Z1-F 3x1.5;
Marking: 1 2 L;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: 1 2 L;
Application: Switching function;
Suitable: for distribution connectors; series and two-way circuits;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: brown;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Fire load: 29,265; MJ
Connector Culoare: brown;
Printing color of mating face: white;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: black;
Printing color of sheathed cable: white;
Halogen-free: Yes;
Greutate: 107,4; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: DE;
GTIN: 4050821310983;
Customs tariff number: 85444290900;
Pret: 26,61 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-3-pole-cod-s-1-m-1-50-mm2-brown-138558