www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; B2CA; SOCKET/PLUG; 3-POLE; COD. B; 5 M; 1,00 MM²; GRAY

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 10; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 23; A
Numar poli: 3;
Total number of potentials: 3;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 6,3 … 8 mm;
Sectiunea transversala a firului: 1; mm²
Connection type: Socket - Plug;
Distanta intre pini: 10 mm / 0.394 inch;
Total length: 5; m
Coding: B;
Mating force of a plug-in connection: approx. 20 … 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 20 … 70 N (depending on pole number);
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);
Connection type: Socket - Plug;
Type of pre-assembled cable: Interconnecting cable;
Cable type: H05Z1Z1-F 3x1;
Marking: 1 2 3;

Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: 1 2 3;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: B2ca;
Contact material: Copper or copper alloy (surface-treated);
Connector Culoare: gray;
Printing color of mating face: black;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: gray;
Printing color of sheathed cable: black;
Halogen-free: Yes;
Greutate: 375,9; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: DE;
GTIN: 4055143758758;
Customs tariff number: 85444290900;
Pret: 109,57 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/pre-assembled-interconnecting-cable-b2ca-socket-plug-3-pole-cod-b-5-m-1-00-mm2-gray-139237