



**WAGO 4-CONDUCTOR FUSE TERMINAL BLOCK; FOR MINI-AUTOMOTIVE BLADE-
STYLE FUSES; PER DIN 7258-3F, ISO 8820-3; WITH TEST OPTION; WITH PUSH-
BUTTON; WITHOUT BLOWN FUSE INDICATION; 2.5 MM²; PUSH-IN CAGE CLAMP®;
2,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-3;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 10; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Push-button; Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 5,2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;

Adancime: 87,5 mm / 3.445 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,197; MJ
Greutate: 9,7; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143902830;
Customs tariff number: 85369095990;
Pret: 22,12 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-fuse-terminal-block-for-mini-automotive-blade-style-fuses-per-din-7258-3f-iso-8820-3-with-test-option-with-push-button-without-blown-fuse-indication-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-139500>