
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO THR PCB TERMINAL BLOCK; LOCKING SLIDES; 0.5 MM²; PIN SPACING 2.54 MM; 6-POLE; CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 0,50 MM²; BLACK

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 32; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tesiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 6; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Slider;
Solid conductor: 0,08 … 0,5 mm² / 28 … 20 AWG;
Fine-stranded conductor: 0,08 … 0,5 mm² / 28 … 20 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 mm²;
Strip length: 5 … 6 mm / 0.2 … 0.24 inch;
Conductor connection direction to PCB: 40; °
Numar poli: 6;
Numar total de conexiuni: 6;
Total number of potentials: 6;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Note (conductor cross-section): Terminating 0.75 mm²/18 AWG conductors is possible; however insulation diameter allows only every other clamping unit to be terminated with this conductor size.;
Distanta intre pini: 2,54 mm / 0.1 inch;

Latime: 16,74 mm / 0.659 inch;
Inaltime: 10,9 mm / 0.429 inch;
Inaltime de la fata: 8,1 mm / 0.319 inch;
Adancime: 13 mm / 0.512 inch;
Lungimea pinului de contact: 2,8; mm
Solder pin dimensions: 0,5 x 0,75 mm;
Diametru placat prin gaura (THR): 1,1 (+0,1) mm;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 32; mm
PCB contact: THR;
Solder pin arrangement: over the entire terminal strip (in-line);
Number of solder pins per potential: 2;
Culoare: black;
Material group: III a;
Material izolator: Polyamide 46 (PA 46);
Flammability class per UL94: V2;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 2; g
Temperatura lucru: -60 … +115 °C;
Tip ambalare: bag;
Tara de origine: CH;
GTIN: 4045454472030;
Customs tariff number: 85369010000;
Pret: 18,30 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/thr-pcb-terminal-block-locking-slides-0-5-mm2-pin-spacing-2-54-mm-6-pole-cage-clamp-in-tape-and-reel-packaging-0-50-mm2-black-139544