



WAGO THR MALE HEADER; 1.4 MM Ø SOLDER PIN; STRAIGHT; PIN SPACING 7.5 MM; 2-POLE; LIGHT GRAY

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Tensiune nominala (III/2): 630; V
Tensiune nominala de supratensiune (III/2): 6; kV
Tensiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 6; kV
Curent nominal: 16; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 15; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Numar poli: 2;
Total number of potentials: 2;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 7,5 mm / 0.295 inch;
Latime: 14,7 mm / 0.579 inch;
Inaltime: 21,9 mm / 0.862 inch;
Inaltime de la fata: 19,5 mm / 0.768 inch;
Adancime: 14,4 mm / 0.567 inch;
Lungimea pinului de contact: 2,4; mm
Diametrul pinului de contact: 1,4; mm
Diametru placat prin gaura (THR): 1,6 (+0,1) mm;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for PCB;

Mismating protection: No;

Mating direction to the PCB: 90; °

Locking of plug-in connection: Locking latch;

PCB contact: THR;

Culoare: light gray;

Material group: I;

Material izolator: Polyphthalamide (PPA GF);

Flammability class per UL94: V0;

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;

Fire load: 0,04; MJ

Greutate: 1,7; g

Temperatura lucru: -60 ... +100 °C;

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821396512;

Customs tariff number: 85366990990;

Pret: 3,68 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-straight-pin-spacing-7-5-mm-2-pole-light-gray-139691>