



**WAGO THT FEMALE HEADER; 0.4 X 1.3 MM SOLDER PIN; STRAIGHT; PIN SPACING
7.5 MM; 5-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Tensiune nominala (III/2): 630; V
Tensiune nominala de supratensiune (III/2): 6; kV
Tensiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 6; kV
Curent nominal: 16; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 15; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Numar poli: 5;
Total number of potentials: 5;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 7,5 mm / 0.295 inch;
Latime: 35 mm / 1.378 inch;
Inaltime: 19,8 mm / 0.78 inch;
Inaltime de la fata: 16,2 mm / 0.638 inch;
Adancime: 13,6 mm / 0.535 inch;
Lungimea pinului de contact: 3,6; mm
Solder pin dimensions: 0,4 x 1,3 mm;
Diametrul de gaurire cu toleranta: 1,5 (+0,1) mm;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for PCB;

Mismating protection: No;

Mating direction to the PCB: 90; °

PCB contact: THT;

Culoare: light gray;

Material group: I;

Material izolator: Polyphthalamide (PPA GF);

Flammability class per UL94: V0;

Contact material: Copper alloy;

Contact plating: tin-plated;

Fire load: 0,156; MJ

Greutate: 6; g

Temperatura lucru: -60 ... +100 °C;

Product Group: 26 (picoMAX);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821164500;

Customs tariff number: 85366990990;

Pret: 20,16 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-female-header-0-4-x-1-3-mm-solder-pin-straight-pin-spacing-7-5-mm-5-pole-light-gray-139715>