



**WAGO SMD PCB TERMINAL BLOCK; PUSH-BUTTON; 0,75 MM<sup>2</sup>; PIN SPACING 4 MM;  
2-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 0,75 MM<sup>2</sup>;  
WHITE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 63; V  
Tensiune nominala de supratensiune (III/3): 2,5; kV  
Tensiune nominala (III/2): 160; V  
Tensiune nominala de supratensiune (III/2): 2,5; kV  
Tensiune nominala (II/2): 320; V  
Tensiune nominala de supratensiune (II/2): 2,5; kV  
Curent nominal: 9; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tensiune nominala UL 1977: 320; V  
Curent nominal UL 1977: 9; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Push-button;  
Solid conductor: 0,2 ... 0,75 mm<sup>2</sup> / 24 ... 18 AWG;  
Fine-stranded conductor: 0,2 ... 0,75 mm<sup>2</sup> / 24 ... 18 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,25 ... 0,34 mm<sup>2</sup>;  
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 0,34 mm<sup>2</sup>;  
Strip length: 7 ... 9 mm / 0.28 ... 0.35 inch;  
Conductor connection direction to PCB: 0; °  
Numar poli: 2;  
Numar total de conexiuni: 2;  
Total number of potentials: 2;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;

Distanța între pini: 4 mm / 0.157 inch;  
Lățime: 7,9 mm / 0.311 inch;  
Înălțime: 4,5 mm / 0.177 inch;  
Adâncime: 13,1 mm / 0.516 inch;  
Reel diameter of tape-and-reel packaging: 330; mm  
Tape Lățime: 24; mm  
PCB contact: SMD;  
Culoare: white;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Copper alloy;  
Contact plating: tin-plated;  
Greutate: 0,5; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 33 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4055143541244;  
Customs tariff number: 85369010000;  
Pret: 3,25 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/smd-pcb-terminal-block-push-button-0-75-mm2-pin-spacing-4-mm-2-pole-push-in-cage-clamp-in-tape-and-reel-packaging-0-75-mm2-white-139868>