



**WAGO COMPACT SPLICING CONNECTOR; FOR ALL CONDUCTOR TYPES; MAX. 6 MM<sup>2</sup>; 5-CONDUCTOR; WITH LEVERS; TRANSPARENT HOUSING; SURROUNDING AIR TEMPERATURE: MAX 85°C (T85); 6,00 MM<sup>2</sup>; TRANSPARENT**

Ratings per: EN 60664;  
Tensiune nominala (II/2): 450; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 41; A  
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;  
Tensiune nominala UL (Use Group C): 600; V  
Curent nominal UL (Use Group C): 30; A  
Certificari: UL 486C;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Lever;  
Connectable conductor materials: Copper;  
Nominal cross-section: 6 mm<sup>2</sup>;  
Solid conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Fine-stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Strip length: 12 ... 14 mm / 0.47 ... 0.55 inch;  
Numar total de conexiuni: 5;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Latime: 36,7 mm / 1.445 inch;  
Inaltime: 10,1 mm / 0.398 inch;  
Adancime: 21,1 mm / 0.831 inch;  
Culoare: transparent;  
Flammability class per UL94: V2;  
Greutate: 7,1; g

Surrounding air temperature (operation): 85 °C;  
Continuous operating temperature: 105 °C;  
Temperature marking per EN 60998: T85;  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4055143715478;  
Customs tariff number: 85369010000;  
Pret: 7,05 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/compact-splicing-connector-for-all-conductor-types-max-6-mm2-5-conductor-with-levers-transparent-housing-surrounding-air-temperature-max-850c-t85-6-00-mm2-transparent-139894>