www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 4-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM²; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 2,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 24; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,08 … 2,5 mm² / 28 … 12 AWG;
Fine-stranded conductor: 0,08 … 4 mm² / 28 … 12 AWG;
Strip length: 6 … 7 mm / 0.24 … 0.28 inch;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 5 mm / 0.197 inch;
Inaltime from upper-edge of DIN-rail: 27,5 mm / 1.083 inch;
Adancime: 55 mm / 2.165 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,118; MJ
Greutate: 7,3; g
Product Group: 16 (Rail Mounted Terminal Block with CCC);

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454094621;
Customs tariff number: 85369010000;
Pret: 7,24 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/4-conductor-through-terminal-block-2-5-mm2-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-2-50-mm2-gray-139947