
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO DOUBLE-DECK TERMINAL BLOCK; 4-CONDUCTOR GROUND TERMINAL BLOCK; PE; WITHOUT MARKER CARRIER; SUITABLE FOR EX E II APPLICATIONS; INTERNAL COMMONING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 2,5 mm²;
Solid conductor: 0,25 … 4 mm² / 22 … 12 AWG;
Solid conductor; push-in termination: 0,75 … 4 mm² / 18 … 12 AWG;
Fine-stranded conductor: 0,25 … 4 mm² / 22 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 1 … 2,5 mm² / 18 … 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1 … 2,5 mm² / 18 … 12 AWG;
Strip length: 10 … 12 mm / 0.39 … 0.47 inch;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar nivele: 2;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Latime: 5,2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 51,7 mm / 2.035 inch;
Adancime: 69,7 mm / 2.744 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Potential marking: PE;
Marking level: Center/side marking;

Culoare: green-yellow;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,206; MJ
Greutate: 13,5; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918691147;
Customs tariff number: 85369010000;
Pret: 30,67 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/double-deck-terminal-block-4-conductor-ground-terminal-block-pe-without-marker-carrier-suitable-for-ex-e-ii-applications-internal-commoning-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-green-yellow-140013