



### WAGO LUMINAIRE DISCONNECT CONNECTOR; 3-POLE; 4,00 MM<sup>2</sup>; YELLOW

Ratings per: EN 60998;  
Tensiune nominala (II/2): 400; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 6; A  
Ratings per: EN 61984;  
Connection type (1): Plug;  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper;  
Solid conductor: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Stranded conductor: 1,5 ... 2,5 mm<sup>2</sup> / 16 ... 12 AWG;  
Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;  
Numar poli: 3;  
Connection type 2: Socket;  
Solid conductor 2: 0,75 mm<sup>2</sup> / 18 AWG;  
Strip length 2: 9 ... 11 mm / 0.35 ... 0.43 inch;  
Numar total de conexiuni: 9;  
Total number of potentials: 3;  
Latime: 19 mm / 0.748 inch;  
Inaltime: 13,2 mm / 0.52 inch;  
Adancime: 42 mm / 1.654 inch;  
Culoare: yellow;  
Fire load: 0,144; MJ  
Greutate: 6,9; g  
Product Group: 8 (Misc. Chassis Mount Blocks);  
Tip ambalare: BOX;  
Tara de origine: CN;

GTIN: 4045454671815;

Customs tariff number: 85366990990;

Pret: 7,96 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/luminaire-disconnect-connector-3-pole-4-00-mm2-yellow-140018>