



**WAGO 3-CONDUCTOR GROUND TERMINAL BLOCK; 10 MM<sup>2</sup>; SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 10,00 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 10 mm<sup>2</sup>;

Solid conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;

Solid conductor; push-in termination: 4 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;

Fine-stranded conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;

Fine-stranded conductor; with insulated ferrule: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;

Strip length: 17 ... 19 mm / 0.67 ... 0.75 inch;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 10 mm / 0.394 inch;

Inaltime from upper-edge of DIN-rail: 36,9 mm / 1.453 inch;

Adancime: 89 mm / 3.504 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,376; MJ  
Greutate: 35,6; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4017332076340;  
Customs tariff number: 85369010000;  
Pret: 35,47 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-ground-terminal-block-10-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-10-00-mm2-green-yellow-140048>