



**WAGO SOCKET; WITH AUTOMATIC CUTTING OF LIVE CONDUCTOR; 3-POLE;
ORANGE**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Tensiune nominala (III/2): 630; V
Tensiune nominala de supratensiune (III/2): 6; kV
Tensiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 6; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 10; A
Tehnologie conexiune: IDC;
Fine-stranded conductor: 0,75 ... 1,5 mm² / 18 ... 16 AWG;
Numar poli: 3;
Total number of potentials: 3;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Latime: 26,5 mm / 1.043 inch;
Inaltime: 27 mm / 1.063 inch;
Adancime: 23 mm / 0.906 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Culoare: orange;

Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Brass;
Contact plating: tin-plated;
Fire load: 0,169; MJ
Greutate: 7,1; g
Temperatura lucru: -60 ... +85 °C;
Product Group: 13 (Misc. Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821429715;
Customs tariff number: 85366990990;
Pret: 16,17 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/socket-with-automatic-cutting-of-live-conductor-3-pole-orange-140101>