www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO SERVICE CONNECTOR; PUSH-BUTTON ON BOTH SIDES; LIGHTING SIDE: FOR ALL CONDUCTOR TYPES; INST. SIDE: FOR ALL CONDUCTOR TYPES; 224 SERIES; MAX. 2.5 MM²; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM²; GRAY

Ratings per: EN 60664;
Tesiune nominala (II/2): 400; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 24; A
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Push-in;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 0,5 … 2,5 mm² / 20 … 16 AWG;
Fine-stranded conductor: 0,5 … 2,5 mm² / 20 … 16 AWG;
Strip length: 9 … 11 mm / 0.35 … 0.43 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Latime: 8 mm / 0.315 inch;
Inaltime: 15,5 mm / 0.61 inch;
Adancime: 42 mm / 1.654 inch;
Culoare: gray;
Fire load: 0,099; MJ
Greutate: 4,6; g
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4044918818407;
Customs tariff number: 85369010000;

Pret: 1,64 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/service-connector-push-button-on-both-sides-lighting-side-for-all-conductor-types-inst-side-for-all-conductor-types-224-series-max-2-5-mm2-surrounding-air-temperature-max-600c-2-50-mm2-gray-140133