www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO SMD PCB TERMINAL BLOCK; PUSH-BUTTON; 0.75 MM²; PIN SPACING 4 MM; 3-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 0,75 MM²; WHITE

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 63; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tesiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 9; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tensiune nominala UL 1977: 320; V
Curent nominal UL 1977: 9; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-button;
Solid conductor: 0,2 … 0,75 mm² / 24 … 18 AWG;
Fine-stranded conductor: 0,2 … 0,75 mm² / 24 … 18 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 … 0,34 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 … 0,34 mm²;
Strip length: 7 … 9 mm / 0.28 … 0.35 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 3;
Numar total de conexiuni: 3;
Total number of potentials: 3;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;

Distanta intre pini: 4 mm / 0.157 inch;
Latime: 11,9 mm / 0.469 inch;
Inaltime: 4,5 mm / 0.177 inch;
Adancime: 13,1 mm / 0.516 inch;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 24; mm
PCB contact: SMD;
Culoare: white;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy;
Contact plating: tin-plated;
Greutate: 1,1; g
Temperatura lucru: -60 … +105 °C;
Product Group: 33 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4055143135085;
Customs tariff number: 85369010000;
Pret: 4,82 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/smd-pcb-terminal-block-push-button-0-75-mm2-pin-spacing-4-mm-3-pole-push-in-cage-clamp-in-tape-and-reel-packaging-0-75-mm2-white-140157