www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO SUPPLY MODULE; FOR FLAT CABLE; 5 X 16 MM²; 5-POLE; 16,00 MM²; BLACK

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 690; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 76; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Screw-type connection;
Tip actionare: Operating tool;
Numar poli: 5;
Tehnologie conexiune 2: IDC;
Numar total de conexiuni: 5;
Total number of potentials: 5;
Latime: 85 mm / 3.346 inch;
Inaltime: 90 mm / 3.543 inch;
Adancime: 200 mm / 7.874 inch;
Mating force of a plug-in connection: approx. 30 … 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 … 20 N;
Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 25 A, tested (4 mm²/AWG 12);
Protection type: IP20;
Note on protection type: IP65 mit Schraubanschluss/Blindstopfen;
Suitable: for flat cable 5 x 16 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;

Culoare: black;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 11,88; MJ
Greutate: 872,9; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free) PVC flat cable for temperatures –15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454006389;
Customs tariff number: 85369010000;
Pret: 716,28 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/supply-module-for-flat-cable-5-x-16-mm2-5-pole-16-00-mm2-black-140160