



WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 16 MM²; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 16,00 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 16 mm²;

Solid conductor: 0.5 ... 16 mm² / 20 ... 6 AWG;

Solid conductor; push-in termination: 6 ... 16 mm² / 14 ... 6 AWG;

Fine-stranded conductor: 0.5 ... 25 mm² / 20 ... 4 AWG;

Fine-stranded conductor; with insulated ferrule: 6 ... 16 mm² / 10 ... 6 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 6 ... 16 mm² / 10 ... 6 AWG;

Strip length: 18 ... 20 mm / 0.71 ... 0.79 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 12 mm / 0.472 inch;

Inaltime from upper-edge of DIN-rail: 40.8 mm / 1.606 inch;

Adancime: 85.7 mm / 3.374 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);

Greutate: 43,6; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4045454725112;

Customs tariff number: 85369010000;

Pret: 34,61 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-ground-terminal-block-16-mm2-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-16-00-mm2-green-yellow-140202>