



WAGO MALE CONNECTOR WITH CONNECT. FOR GROUND; 7-POLE; 2,50 MM²;
WHITE

Ratings per: IEC/EN 61984;
Tensiune nominala (III/2): 500; V
Tensiune nominala de supratensiune (III/2): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: PUSH WIRE®;
Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;
Numar poli: 7;
Numar tipuri de conexiuni: 1;
Latime: 35 mm / 1.378 inch;
Inaltime de la fata: 18 mm / 0.709 inch;
Adancime: 39 mm / 1.535 inch;
Culoare: white;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,273; MJ
Greutate: 19,4; g
Temperature stability: 105; °C
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: BOX;
Tara de origine: PL;

GTIN: 4044918546706;
Customs tariff number: 85369010000;
Pret: 15,26 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/male-connector-with-connect-for-ground-7-pole-2-50-mm2-white-140356>