



**WAGO QUADRUPLE-DECK RAIL-MOUNTED TERMINAL BLOCK; RAIL-MOUNTED
TERMINAL BLOCK FOR ELECTRIC MOTOR WIRING; L1 - L2 - L3 - PE; WITHOUT
MARKER CARRIER; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE
CLAMP®; 2,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 20; A

Curent nominal 2: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 20; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 20; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Number of connection points (connection type): 2;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Number of connection points: 2;

Number of connection points: 2;

Number of connection points: 1;

Numar total de conexiuni: 7;
Total number of potentials: 4;
Numar nivele: 4;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Latime: 5,2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 83,9 mm / 3.303 inch;
Adancime: 103,5 mm / 4.075 inch;
Tip montaj: DIN-35 rail;
Potential marking: L1 - L2 - L3 - PE;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,41; MJ
Greutate: 25,3; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821579410;
Customs tariff number: 85369010000;
Pret: 37,00 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/quadruple-deck-rail-mounted-terminal-block-rail-mounted-terminal-block-for-electric-motor-wiring-l1-l2-l3-pe-without-marker-carrier-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-140479>