



**WAGO 2-CONDUCTOR/2-PIN DOUBLE-DECK CARRIER TERMINAL; 2-  
CONDUCTOR/1-PIN THROUGH TERMINAL BLOCK; L/L; FOR DIN-RAIL 35 X 15 AND  
35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 6;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 39,8 mm / 1.567 inch;

Adancime: 91 mm / 3.583 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: L/L;

Marking level: Side marking;

Culoare: gray;

Greutate: 13,5; g

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143343251;

Customs tariff number: 85366990990;

Pret: 16,60 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-2-pin-double-deck-carrier-terminal-2-conductor-1-pin-through-terminal-block-1-l-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-140727>