www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO TAP-OFF MODULE; 2-POLE; FOR PLUG CONNECTORS AND WIRE ASSEMBLIES WINSTA® KNX CODING F; 1 NM TIGHTENING TORQUE; WITH SCREW-TYPE CONNECTION; LIGHT GRAY

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: IDC;
Tip actionare: Operating tool;
Numar poli: 2;
Latime: 39,4 mm / 1.551 inch;
Inaltime: 25 mm / 0.984 inch;
Adancime: 44 mm / 1.732 inch;
Technologie: KNX;
Coding: F;
Mating force of a plug-in connection: approx. 10 … 15 N;
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 … 20 N;
Number of mating cycles: ?200;
Marking: 1+ 2-;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: 1+ 2-;
Application: KNX;

Suitable: for flat cable 5 x 2.5 mm² + 2 x 1.5 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Greutate: 19; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free) PVC flat cable for temperatures –15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454267308;
Customs tariff number: 85366990990;
Pret: 106,18 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/tap-off-module-2-pole-for-plug-connectors-and-wire-assemblies-winsta-knx-coding-f-1-nm-tightening-torque-with-screw-type-connection-light-gray-140772