



WAGO TAP-OFF MODULE; 2-POLE; FOR PLUG CONNECTORS AND WIRE ASSEMBLIES WINSTA® KNX CODING F; 1 NM TIGHTENING TORQUE; WITH SCREW-TYPE CONNECTION; LIGHT GRAY

Note on Contact Resistance: approx. 1 m Ω of contact resistance approx. 0.25 m Ω contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 50; V

Tensiune nominala de supratensiune (III/3): 0,8; kV

Curent nominal: 3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: IDC;

Tip actionare: Operating tool;

Numar poli: 2;

Latime: 39,4 mm / 1.551 inch;

Inaltime: 25 mm / 0.984 inch;

Adancime: 44 mm / 1.732 inch;

Technologie: KNX;

Coding: F;

Mating force of a plug-in connection: approx. 10 ... 15 N;

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ?200;

Marking: 1+ 2-;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Potential marking: 1+ 2-;

Application: KNX;

Suitable: for flat cable 5 x 2.5 mm² + 2 x 1.5 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Greutate: 19; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
PVC flat cable for temperatures -15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454267308;
Customs tariff number: 85366990990;
Pret: 105,38 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tap-off-module-2-pole-for-plug-connectors-and-wire-assemblies-winsta-knx-coding-f-1-nm-tightening-torque-with-screw-type-connection-light-gray-140772>