



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; WITH PIVOTING FUSE HOLDER;
FOR 5 X 20 MM MINIATURE METRIC FUSE; WITHOUT BLOWN FUSE INDICATION;
FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²; PUSH-IN CAGE CLAMP®; 6,00 MM²;
GRAY**

Ratings per: IEC/EN 60947-7-3;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 10; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 15; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 15; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 2,5 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 10 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross

section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 7,5 mm / 0.295 inch;

Inaltime from upper-edge of DIN-rail: 59 mm / 2.323 inch;

Adancime: 96,3 mm / 3.791 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,46; MJ

Greutate: 24,9; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4045454821166;

Customs tariff number: 85369095990;

Pret: 29,16 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-fuse-terminal-block-with-pivoting-fuse-holder-for-5-x-20-mm-miniature-metric-fuse-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-push-in-cage-clamp-6-00-mm2-gray-140832>