



**WAGO GROUND CONDUCTOR DISCONNECT TERMINAL BLOCK; WITH TEST  
OPTION; WITH ORANGE DISCONNECT LINK; 24 V; 6 MM<sup>2</sup>; CAGE CLAMP®; 6,00  
MM<sup>2</sup>; GRAY**

Operation status indicator: 24 V;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.2 ... 6 mm<sup>2</sup> / 24 ... 10 AWG;  
Fine-stranded conductor: 0.2 ... 6 mm<sup>2</sup> / 24 ... 10 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 4;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 16 mm / 0.63 inch;  
Inaltime from upper-edge of DIN-rail: 37 mm / 1.457 inch;  
Adancime: 85 mm / 3.346 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 40,8; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821228912;  
Customs tariff number: 85365080900;

Pret: 177,36 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ground-conductor-disconnect-terminal-block-with-test-option-with-orange-disconnect-link-24-v-6-mm2-cage-clamp-6-00-mm2-gray-141202>