



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 35 MM<sup>2</sup>; WITH INTEGRATED  
END PLATE; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5;  
CAGE CLAMP®; 35,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 1000; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 125; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Open Tool Slot;  
Connectable conductor materials: Copper;  
Solid conductor: 6 ... 35 mm<sup>2</sup> / 8 ... 2 AWG;  
Strip length: 23 mm / 0.91 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 16 mm / 0.63 inch;  
Inaltime from upper-edge of DIN-rail: 44,5 mm / 1.752 inch;  
Adancime: 114 mm / 4.488 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 1,103; MJ  
Greutate: 86,6; g  
Product Group: 17 (TOP JOB installation terminal blocks);

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454400576;  
Customs tariff number: 85369010000;  
Pret: 57,71 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-35-mm2-with-integrated-end-plate-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-35-00-mm2-gray-141243>