



**WAGO 4-CONDUCTOR TERMINAL BLOCK; WITHOUT PUSH-BUTTONS; WITH  
SNAP-IN MOUNTING FOOT; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5  
MM Ø; 4 MM<sup>2</sup>; CAGE CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Tesiune nominala (III/3): 630; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 12 mm / 0.472 inch;

Inaltime de la fata: 23 mm / 0.906 inch;

Adancime: 33.5 mm / 1.319 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,113; MJ

Greutate: 6,9; g

Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;

Tara de origine: CN;  
GTIN: 4044918638890;  
Customs tariff number: 85369010000;  
Pret: 6,25 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-terminal-block-without-push-buttons-with-snap-in-mounting-foot-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-4-mm2-cage-clamp-4-00-mm2-gray-141254>