www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO LIGHTING CONNECTOR; PUSH-BUTTON ON LIGHTING SIDE; LIGHTING SIDE: FOR ALL CONDUCTOR TYPES; INST. SIDE: FOR SOLID CONDUCTORS; 224 SERIES; MAX. 2.5 MM²; SURROUNDING AIR TEMPERATURE: MAX 75°C; 2,50 MM²; BLACK

Ratings per: EN 60664;
Tesiune nominala (II/2): 400; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 24; A
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;
Connection type (1): Installation side;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 1 … 2,5 mm² / 14 … 12 AWG;
Strip length: 9 … 11 mm / 0.35 … 0.43 inch;
Connection type 2: Lighting side;
Tehnologie conexiune 2: CAGE CLAMP®;
Number of connection points: 1;
Solid conductor 2: 0,5 … 2,5 mm² / 20 … 16 AWG;
Fine-stranded conductor 2: 0,5 … 2,5 mm² / 20 … 16 AWG;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Latime: 8 mm / 0.315 inch;
Inaltime: 15,5 mm / 0.61 inch;
Adancime: 20,4 mm / 0.803 inch;
Culoare: black;
Fire load: 0,051; MJ

Greutate: 2,2; g
Continuous operating temperature: 120 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4044918584050;
Customs tariff number: 85369010000;
Pret: 1,79 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lighting-connector-push-button-on-lighting-side-lighting-side-for-all-conductor-types-inst-side-for-solid-conductors-224-series-max-2-5-mm2-surrounding-air-temperature-max-750c-2-50-mm2-black-141261