



WAGO SNAP-ON TYPE CONDUCTOR SUPPORT; 4-POLE

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/2): 500; V
Tensiune nominala de supratensiune (III/2): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: PUSH WIRE®;
Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;
Numar poli: 4;
Numar total de conexiuni: 8;
Total number of potentials: 4;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Latime: 42 mm / 1.654 inch;
Inaltime: 15.5 mm / 0.61 inch;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,269; MJ
Greutate: 15,9; g
Temperature stability: 105; °C
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: bag;
Tara de origine: PL;

GTIN: 4045454415471;
Customs tariff number: 85369010000;
Pret: 16,11 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/snap-on-type-conductor-support-4-pole-141269>