
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO PRE-ASSEMBLED Y-CABLE; CCA; 2 X PLUG/SOCKET; 3-POLE + 2-POLE/5-POLE; COD. A/I; H05Z1Z1-F 2 X 1,50 MM²; H05Z1Z1-F 3G 2.5 MM²; 0.5 M; 1,50 MM²; BLACK/BLUE

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 23; A
Numar poli: 3;
Pole number 2: 2;
Pole number 3: 5;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 6,8 … 8,6 mm;
Sectiunea transversala a firului: 1,5; mm²
Sectiunea transversala a firului (2): 2,5; mm²
Connection type: MIDI plug; MINI plug - MIDI socket;
Durchmesser der Mantelleitung 2: 9,2 … 11,4 mm;
Distanta intre pini: 10 mm / 0.394 inch;
Technologie: DALI;
Coding: A;
Mating force of a plug-in connection: approx. 20 … 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 20 … 70 N (depending on pole number);
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);
Connection type: MIDI plug; MINI plug - MIDI socket;

Type of pre-assembled cable: Y-cable;
Cable type: H05Z1Z1-F 2x1.5;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Application: General mains applications;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: black/blue;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Cca;
Contact material: Copper or copper alloy (surface-treated);
Greutate: 158,3; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: DE;
GTIN: 4055143811996;
Customs tariff number: 85444290900;
Pret: 158,47 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/pre-assembled-y-cable-cca-2-x-plug-socket-3-pole-2-pole-5-pole-cod-a-i-h05z1z1-f-2-x-1-50-mm2-h05z1z1-f-3g-2-5-mm2-0-5-m-1-50-mm2-black-blue-141486