



WAGO MALE CONNECTOR; 7-POLE; 2,50 MM²; WHITE

Ratings per: IEC/EN 61984;
Tensiune nominala (III/2): 500; V
Tensiune nominala de supratensiune (III/2): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Connection type (1): PUSH WIRE® connection;
Tehnologie conexiune: PUSH WIRE®;
Number of connection points (connection type): 1;
Solid conductor: 1,5 ... 2,5 mm² / 16 ... 14 AWG;
Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;
Connection type 2: PUSH WIRE® connection;
Tehnologie conexiune 2: PUSH WIRE®;
Number of connection points: 1;
Solid conductor 2: 0,75 ... 1,5 mm² / 18 ... 16 AWG;
Strip length 2: 11 ... 12 mm / 0.43 ... 0.47 inch;
Numar tipuri de conexiuni: 2;
Numar nivele: 2;
Latime: 35 mm / 1.378 inch;
Inaltime de la fata: 18 mm / 0.709 inch;
Adancime: 39 mm / 1.535 inch;
Culoare: white;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;
Fire load: 0,281; MJ
Greutate: 19,6; g
Temperature stability: 105; °C
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4050821307914;
Customs tariff number: 85369010000;
Pret: 15,26 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/male-connector-7-pole-2-50-mm2-white-141524>