



**WAGO MULTILEVEL INSTALLATION TERMINAL BLOCK; 6 MM²; L/L/PE; PUSH-IN
CAGE CLAMP[®]; 4,00 MM²; GRAY**

Ratings (note): Potential – ground;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 36; A

Ratings (note) 2: Potential – potential;

Tensiune nominala (III/3) 2: 400; V

Tensiune nominala de supratensiune (III/3) 2: 6; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP[®];

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm²;

Solid conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Solid conductor; push-in termination: 1,5 ... 6 mm² / 14 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm² / 18 ... 12 AWG;

Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;

Numar total de conexiuni: 5;

Total number of potentials: 3;

Numar nivele: 3;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 6,2 mm / 0.244 inch;

Inaltime from upper-edge of DIN-rail: 41,7 mm / 1.642 inch;

Adancime: 124 mm / 4.882 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Potential marking: L/L/PE;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 30,2; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143042253;
Customs tariff number: 85369010000;
Pret: 29,59 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/multilevel-installation-terminal-block-6-mm2-1-l-pe-push-in-cage-clamp-4-00-mm2-gray-141576>