
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO PLUG; WITH STRAIN RELIEF HOUSING; 2-POLE; COD. F; LIGHT GRAY

Note on Contact Resistance: ? approx. 3m? contact resistance ;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Conductor diameter: 0,8 mm;
Strip length: 9 mm / 0.35 inch;
Note (strip length): see also packaging or instructions;
Numar poli: 2;
Numar total de conexiuni: 2;
Total number of potentials: 2;
Connectable sheathed cable diameter: 5 … 7 mm;
Conductor entry direction to mating direction: 0; °
Latime: 14,1 mm / 0.555 inch;
Adancime: 47,5 mm / 1.87 inch;
Technologie: KNX;
Coding: F;
Mating force of a plug-in connection: approx. 10 … 15 N;
Retention force of a plug-in connection: Locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 … 20 N;
Number of mating cycles: ?200;
Marking: 1+ 2-;
Protection type: IP20;
Note on protection type: Only when mated and secured with a strain relief housing (These compact

connectors are not designed for use in open, easily accessible areas.);
Potential marking: 1+ 2-;
Application: KNX;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for conductor;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Strain relief: strain relief housing;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy (surface-treated);
Fire load: 0,171; MJ
Greutate: 5,7; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454267452;
Customs tariff number: 85366990990;
Pret: 37,40 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/plug-with-strain-relief-housing-2-pole-cod-f-light-gray-141655