
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 2.5 MM²; WITH TEST PORT; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 2,50 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Lever; Push-button;
Tip actionare 2: Push-in; Push-button; Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 2.5 mm²;
Solid conductor: 0.25 … 4 mm² / 22 … 12 AWG;
Solid conductor; push-in termination: 0.75 … 4 mm² / 18 … 12 AWG;
Fine-stranded conductor: 0.25 … 4 mm² / 22 … 12 AWG;
Fine-stranded conductor; with insulated ferrule: 1 … 2.5 mm² / 18 … 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1 … 2.5 mm² / 18 … 12 AWG;
Strip length: 10 … 12 mm / 0.39 … 0.47 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 5.2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 32.9 mm / 1.295 inch;
Adancime: 63.8 mm / 2.512 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;

Culoare: green-yellow;
Material izolator: Polyamide 66 (PA 66);
Greutate: 9,9; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143741903;
Customs tariff number: 85369010000;
Pret: 24,98 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-conductor-ground-terminal-block-2-5-mm2-with-test-port-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-2-50-mm2-green-yellow-141759